


KWC F5S-Therm


Self-closing thermostatic wall-mounted mixer with hand shower connection and pre-fitted hygiene unit

Modell-Linie: F5S | F5ST2111

Showers | Self closing showers







KWC-No.

3600008423

F5S-Therm self-closing thermostatic mixer DN 15 for wall mounting, for shower facilities. Hydraulically controlled, connects to hot water and cold water. Pre-fitted hygiene unit with C-module including control electronics, 6 V lithium battery (CR-P2) and solenoid valve cartridge for automatic hygiene flushing and saving of statistical data. FRAMIC self-closing cartridge, hydraulically controlled, low maintenance and stagnation free, with ceramic disc technology, self closing, flow pressure independent due to medium-independent design. Fully adjustable flow duration. Thermostat with metal handle with adjustable and turn-proof temperature stop, with option

for performance of manual thermal disinfection. Scald-protected, safe-touch housing with hand shower connection, G 1/2 B. All-metal construction, polished chromium-plated brass. With adjustable and lockable connections with backflow preventers and strainers, fully covered by depth-adjustable screw rosettes. Activated hygiene flushing, fixed interval of 24 hours. With option for radio-controlled parameterisation, read-out of statistical data, realisation of predefined calendar functions as well as grouping of taps to perform predefined control functions via the necessary app.



Technical Data

lechnical Data	
additional connections	
with backflow preventer	
circulation	
compatible A3000 open	
connection with pay water disp	
default automatic hygiene flus	
with filter	
adjustable flow time	
functional principle	
for hand shower	
hygiene flushing	
diameter nominal	
inlet size	
Locking mechanism	
material fitting	
maximum flow time	
minimum flow pressure	
minimum flow time	
type of mixing	
number of batteries	
Parameterization	
power supply connection	

no	
yes	
no	
no	
not possible	
fixed interval 24 hours	
yes	
yes	
hydraulic self-closing	
no	
yes	
DN 15	
G 1/2 B	
Top section, ceramic	
brass-look	
35 Seconds	
1 bar	
5 Seconds	
with thermostat	
1	
арр	
Battery 6 V	















KWC F5S-Therm

Self-closing thermostatic wall-mounted mixer with hand shower connection and pre-fitted hygiene unit

Modell-Linie: F5S | F5ST2111 Showers | Self closing showers

protective system IP with rosettes/cover plate protective shutdown shower pipe draining sound insulation surface finish fitting surface treatment fitting temperature limit thermal disinfection with transformer/power supply type of batteries type of operation type of shower water connection position of water connection Accent colour Basic colour protective system IP yes no chromed polished polished yes manual polished chromed polished polished	Type of power supply	Battery
protective shutdown shower pipe draining sound insulation surface finish fitting surface treatment fitting temperature limit tyes thermal disinfection with transformer/power supply type of batteries type of mounting type of operation type of shower water connection position of water connection Accent colour no no chromed polished yes thermal disinfection manual manual manual manual manual manual manual manual operation wall fitting S-connections from backside none	protective system IP	IP59K
shower pipe draining sound insulation surface finish fitting chromed surface treatment fitting polished temperature limit thermal disinfection manual with transformer/power supply type of batteries CR-P2 Lithium battery 6V type of mounting type of operation type of shower wall fitting water connection position of water connection Accent colour no no no no chromed polished yes manual polished CR-P2 Lithium battery wall mounting manual operation wall fitting S-connections from backside none	with rosettes/cover plate	yes
sound insulation surface finish fitting chromed surface treatment fitting polished temperature limit yes thermal disinfection manual with transformer/power supply type of batteries CR-P2 Lithium battery 6V type of mounting type of operation type of shower wall fitting water connection position of water connection Accent colour no chromed no chromed CR-P2 Ves manual yes manual manual manual manual manual operation manual operation from backside none	protective shutdown	no
surface finish fitting surface treatment fitting polished temperature limit yes thermal disinfection manual with transformer/power supply type of batteries CR-P2 Lithium battery 6V type of mounting type of operation manual operation type of shower wall fitting sections position of water connection Accent colour chromed chromed chromed polished chromed polished yes manual CR-P2 Lithium battery 6V wall mounting manual operation sections from backside none	shower pipe draining	no
surface treatment fitting temperature limit thermal disinfection with transformer/power supply type of batteries CR-P2 Lithium battery 6V type of mounting type of operation type of shower wall fitting water connection position of water connection Accent colour polished po	sound insulation	no
temperature limit thermal disinfection with transformer/power supply type of batteries CR-P2 Lithium battery 6V type of mounting type of operation type of shower wall fitting water connection position of water connection Accent colour yes manual manual manual peration wall fitting S-connections from backside none	surface finish fitting	chromed
thermal disinfection manual with transformer/power supply no type of batteries CR-P2 Lithium battery 6V type of mounting wall mounting type of operation manual operation type of shower wall fitting water connection S-connections position of water connection from backside Accent colour none	surface treatment fitting	polished
with transformer/power supply type of batteries CR-P2 Lithium battery 6V type of mounting wall mounting type of operation type of shower wall fitting water connection position of water connection Accent colour noe	temperature limit	yes
type of batteries CR-P2 Lithium battery 6V type of mounting type of operation type of shower wall fitting water connection position of water connection Accent colour CR-P2 Lithium battery 6V wall mounting manual operation wall fitting S-connections from backside none	thermal disinfection	manual
type of mounting type of operation type of shower wall fitting water connection position of water connection Accent colour wall mounting manual operation wall fitting S-connections from backside none	with transformer/power supply	no
type of operation manual operation type of shower wall fitting water connection S-connections position of water connection from backside Accent colour none	type of batteries	CR-P2 Lithium battery 6V
type of shower wall fitting water connection S-connections position of water connection from backside Accent colour none	type of mounting	wall mounting
water connection S-connections position of water connection from backside Accent colour none	type of operation	manual operation
position of water connection from backside Accent colour none	type of shower	wall fitting
Accent colour none	water connection	S-connections
	position of water connection	from backside
Basic colour chrome-look (glossy)	Accent colour	none
	Basic colour	chrome-look (glossy)

Optional Accessories





Hand shower

2030051216 ACXX2007

Shower bracket

2030051217 ACXX2008