


## **KWC** F5S-Therm Self-closing thermostat wall-mounted mixer

#### Modell-Linie: F5S | F5ST1102

Taps | Self closing taps





| KWC-No.                                | spout projection |
|----------------------------------------|------------------|
| <b>3600008676</b><br>Projection 195 mm | 195 mm           |
| <b>3600008675</b><br>Projection 135 mm | 135 mm           |
| <b>3600008677</b><br>Projection 255 mm | 255 mm           |

F5S-Therm self-closing thermostatic mixer DN 15 for wall mounting with lockable swivelling outlet, for sanitary facilities. Hydraulically controlled, connects to hot water and cold water. With mechanism for optional hygiene unit with C-module for automatic hygiene flushing and readout of statistical data. FRAMIC self-closing cartridge, hydraulically controlled, low maintenance and stagnation free, with ceramic disc technology, self closing, flow pressure independent due to medium-independent design. Fully adjustable flow duration. Thermostat with metal handle with adjustable and turn-proof temperature stop, with option for performance of manual thermal disinfection. Scald-protected, safe-touch housing, all-metal construction, polished chromium-plated brass. Laminar jet controller with integrated flow rate controller 6.0 /min. With adjustable and lockable connections with backflow preventers and strainers, fully covered by depth-adjustable screw rosettes. Projection 195 mm.

#### Technical Data

| compatible A3000 open     |  |
|---------------------------|--|
|                           |  |
| depressurised             |  |
| adjustable flow time      |  |
| functional principle      |  |
| hygiene flushing          |  |
| dia meter nominal         |  |
| inlet size                |  |
| Locking mechanism         |  |
| material fitting          |  |
| type of mixing            |  |
| Pop-up waste set          |  |
| protective shutdown       |  |
| sound insulation          |  |
| Spout                     |  |
| spout projection          |  |
| surface finish fitting    |  |
| surface treatment fitting |  |
| temperature limit         |  |
| thermal disinfection      |  |
| type of mounting          |  |

| no                     |   |
|------------------------|---|
| no                     |   |
| yes                    |   |
| hydraulic self-closing |   |
| prepared               |   |
| DN 15                  |   |
| G 1/2 B                |   |
| Top section, ceramic   |   |
| brass-look             |   |
| with thermostat        |   |
| no                     |   |
| no                     |   |
| no                     |   |
| rotating, bottom       |   |
| 195 mm                 |   |
| chromed                |   |
| polished               |   |
| yes                    |   |
| manual                 | _ |
| wall mounting          |   |

# NEW

ſ



### KWC F5S-Therm Self-closing thermostat wall-mounted mixer

# **Modell-Linie: F5S | F5ST1102** Taps | Self closing taps

| manual operation     |
|----------------------|
| bib tap              |
| S-connections        |
| none                 |
| chrome-look (glossy) |
| -                    |

#### **Optional Accessories**





#### Theft-proof housing for aerator

**2000104778** ZTAPS0005

Hygiene unit for compatible KWC self-closing thermostatic wall-mounted mixers

**3600008376** ACST9002