


KWC MIRA

Wash place unit Water-Soap-Paper towel dispenser

Modell-Linie: MIRA | MIRX102B Baby changing tables | All-In-One





KWC-No.

3600009113 With satin surface finish	stainless steel	sto
3600008715 With glossy white surface finish	white	w
3600009114 With matt black surface finish	black	blo

MIRA, Integrated wash place mirror unit with water soap towel for wall mounting, touch free optoelectrical controlled, suitable for premixed water, soap pump for liquid / foam soap and manual paper towel dispenser, illuminated pictograms above the respective sensor position, cabinet housing made of powder coated

Accent colour

s steel	stainless steel
	white
	black

stainless steel, matte black, mirrored door, door hinged at top with gas spring, cylindrical lock with standard key.

Dimensions 600 x 900 x 215 mm (W x H x D)

Accent colour

Technical Data

input supply voltage Hz	50 Hertz (1/second)
filling quantity	1,600
filling quantity uom	ml
lock	key-lock
material	stainless steel
material code	1.4301 Chrome Nickel steel V2A
material thickness	1.2 mm
overall depth	215 mm
overall height	900 mm
overall width	600 mm
protective system IP	IP20
type of mounting	wall mounting
type of operation	sensor operation
type of soap container	integrated refillable tank
Accent colour	black
calculation flow rate cold wat	0.02 l/s
calculation flow rate hot wate	0.02 l/s
diameter nominal	DN 15
inlet size	G 3/8 B
material casing	stainless steel
material code casing	1.4301 Chrome Nickel steel V2A
minimum flow pressure	1 bar

KWC MIRA

Wash place unit Water-Soap-Paper towel dispenser

Modell-Linie: MIRA | MIRX102B Baby changing tables | All-In-One

overall depth	215 mm
overall height	900 mm
overall width	600 mm
power supply connection	230 V AC
power consumption	1,100 Voltampere
Type of power supply	Mains power supply
protective system IP	IP20
Spout	fixed
type of mounting	wall mounting
type of operation	sensor operation
type of sensor	opto-electronic sensor
volume flow rate at 3 bar	0.02 l/s
Accent colour	black
calculation flow rate cold wat	0.02 l/s
calculation flow rate hot wate	0.02 l/s
minimum flow pressure	1 bar
overall depth	215 mm
overall height	900 mm
overall width	600 mm
power supply connection	230 V AC
power consumption	1,100 Voltampere
protective system IP	IP20
volume flow rate at 3 bar	0.02 l/s